



MGX-Series Concrete Vibrators



MGX23 (0.905" dia. head) MGX28 (1.105" dia. head) MGX32 (1.25" dia. head) MGX38 (1.5" dia. head)

**A full series of lightweight
handheld vibrators with
exceptional power**

Construction Starts Here


www.multiquip.com



MGX-Series Concrete Vibrators

Ideal for short pours, walls and footings, the MGX-series of handheld vibrators provides exceptional power in a lightweight, user-friendly package.

- Double-insulated motor housing. No ground necessary.
- Lightweight, die cast aluminum motor case.
- High performance, durable 120V, 280 watt, 3.8 amp universal motor — or choose 220V, 280 watt, 2.1 amp motor
- Front-end closed motor design prevents intrusion of any foreign material.
- Shock absorbing rubber handle grip minimizes vibration and reduces operator fatigue.
- Head/shaft combinations available to fill all your requirements.



Head/Shaft Accessory Specifications*

Model	Head in. (mm)	Frequency vpm (Hz)	Total Length ft. (m)	Weight lb. (kg)
MGX2325	.905 (23)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	5.07 (2.3)
MGX2810	1.10 (28)	12,000 to 15,500 (200 to 258)	4.7 (1.4)	3.08 (1.4)
MGX2825	1.10 (28)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	5.07 (2.3)
MGX3225	1.25 (32)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	3.08 (1.4)
MGX3810	1.5 (38)	12,000 to 15,500 (200 to 258)	4.7 (1.4)	5.07 (2.3)
MGX3825	1.5 (38)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	3.08 (1.4)


Motor Only

Model	Voltage	Watts	Amp.
MGX1	120V	280	3.8
MGX2	220V	280	2.1

MGX Specifications (Complete set — Motor/Head/Shaft)

120 Volt Models	240 Volt Models	Head in. (mm)	Shaft Dia. in. (mm)	Amplitude in. (mm)	Frequency Hz (vpm)	Total Length ft. (m)	Weight lb. (kg)
MGX12325	MGX22325	.905 (23)	.79 (20)	.047 (1.2)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	11.47 (5.2)
MGX12810	MGX22810	1.10 (28)	.98 (25)	.070 (1.8)	12,000 to 15,500 (200 to 258)	4.7 (1.4)	9.48 (4.3)
MGX12825	MGX22825	1.10 (28)	.98 (25)	.070 (1.8)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	11.47 (5.2)
MGX13225	MGX23225	1.25 (32)	.98 (25)	.075 (1.9)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	9.48 (4.3)
MGX13810	MGX23810	1.5 (38)	.98 (25)	.079 (2.0)	12,000 to 15,500 (200 to 258)	4.7 (1.4)	11.47 (5.2)
MGX13825	MGX23825	1.5 (38)	.98 (25)	.079 (2.0)	12,000 to 15,500 (200 to 258)	9.5 (2.9)	9.48 (4.3)

* Most popular configurations. Other sizes/lengths available by special order. Multiquip recommends installation to the motor in a shop environment.



DOUBLE INSULATED — NO GROUND NECESSARY

Your Multiquip dealer is:



MULTIQUIP INC.
 POST OFFICE BOX 6254
 CARSON, CA 90749
 310-537-3700 • 800-421-1244
 FAX: 310-537-3927
 E-MAIL: mq@multiquip.com
 www.multiquip.com